

低電壓感應筆

Non-contact

Voltage Detector



特點

- 當感應到有電壓時,LED燈會閃亮,並且 蜂鳴器會急速響應
- 採取不直接觸設計,保障使用者人身安全
- 可應用在電線斷路的偵測
- 設計有手電筒的功能
- 耗電量小
- 通過CE安規檢驗

規格

• 響應電壓範圍: 50V~1000V AC

• 適用頻率:50~500Hz

• 指示方式:LED和蜂鳴器響應

• 外形尺寸: 142(長) x 28(寬) x 27(高)mm

• 重量:約45g(含電池)

• 使用電池: 1.5V(AAA)電池 x 2(顆)

標準電機有限公司

220台北縣板橋市四維路106號

TEL: (02)2256-3125 FAX: (02)2255-6352

E-mail: sales@sew.com.tw Http://www.sew.com.tw

LVD-15是一種非接觸式低電壓感 應筆,以閃爍的LED和急速的蜂鳴 器響應來告知使用者有交流電壓 (AC V)的存在。

它可以用來偵側插座、照明、燈具 、斷路器、電線、電纜線上的電壓 是否存在,或尋找電線的斷路所在





Test & Measuring Instruments

NON-CONTACT VOLTAGE DETECTOR



DESCRIPTION

The **LVD-15** non-contact Voltage Detector is intended to check for the presence of AC voltage, signaling the user with an intermittent tone and a flashing LFD

The non-contact Voltage Detector is used to detect voltage in outlets, lighting fixtures, circuit breakers, wires, and cables or to find a break in a wire.

FEATURES

- 1. Bright LED and audible alarm sound when voltage is present.
- 2. Designed for non-contact voltage detection. It's safer.
- 3. Can be used to find a break in a wire.
- 4. Flash light function.
- 5. ON/OFF switch for longer battery life.

SPECIFICATIONS

1. Voltage detection: 50V~1000V AC

2. Frequency: 50~500 Hz

3. Measurement category: CAT.Ⅲ 600V

4. Indication: LED and Tone

5. Operating Conditions

Temperature: 0~40°C

Humidity: Less than 80% R.H.

Altitude: 2000m (6500 feet) maximum

6. For indoor use only.

7. Pollution degree: 2

8. Dimension: 142(L) x 28(W) x 27(D) mm

9. Weight: 45g (batteries included)

10. Power supply: 1.5V AAA battery x 2





STANDARD ELECTRIC WORKS CO., LTD.

5F.,NO.105, Jhongcheng Rd., Tucheng Dist.,
New Taipei City 23674, Taiwan (R.O.C.)

TEL: 886-2-22681528 FAX: 886-2-22681529
http://www.sew.com.tw e-mail: sales@sew.com.tw